





SEDA Catalytic Cutter

Special tools





The catalyst converter is regarded as the most profitable part of an end-of-life vehicle. The SEDA CatalyticCutter removes them in just a few seconds without requiring great strength and without damaging it.

The SEDA Catalytic Cutters are the optimal solutions for removing catalysts and exhaust systems. Weber Hydraulik have improved their devices for the specific requirements of recycling companies in conjunction with SEDA offering many sizes and solutions for today's operations.

Our optional mobile stand 360° with catalytic converter catchment tray enables easy transport of the cutter and the motor in order to facilitate the usage significantly and prevent any injuries or damages!





RSU 180 PLUS E-FORCE3

Battery version for RSU160, 180 and 210 available further details on request.



Mobile



Stand S-50336













Schwendter Str. 10 / 6345 Kössen / Tirol / Österreich UID-Nr.: ATU56621622 / FB-Nr.: FN 231790 v / FB-Gericht: Innsbruck Certified company according to DIN EN ISO 9001

+43 5375 6318-0

+43 5375 6318-9 info@seda.at

W: www.seda-international.com







SEDA Catalytic Cutter

Special tools

Hydraulic Cutting Tool





- Compact design
- Strong cutting power
- Optimized cutter profile with special cutting notches
- Easy to replace blades
- Battery powered Cutters working on standard M28 Milwaukee batteries
- (Optional) mobile stand available

- New Xtreme cutter technology
- Low cutting strain due to blade development and design
- Clasps the material to cut
- Shorter blades for better maneuverability

Safety monitoring device according to EN 13204 Handgrip 360° adjustable and removable (Optional) mobile stand for ease of use Special blade shape with several cutting ribs Perfect size

Easy blade replacement for RSU 180 / RSU210









TECHNICAL DETAILS / ORDER LINFORMATIONS

RSX105 RS130 RSX165 RSU180 Plus RSU210 Plus Opening width: 105 mm 130 mm 165 mm 180 mm 210 mm **Cutting force::** 290 kN 480 kN 642 kN 903 kN 1.050 kN Max. Cutting cap.: Ø 22 mm Ø 26 mm Ø 38 mm Ø 35 mm Ø 43 mm Nominal pressure: 70 MPa 55 MPa 70 MPa 70 MPa 70 MPa 84 MPa 84 MPa Test pressure: 84 MPa 70 MPa 84 MPa Weight: 9,3 kg 15,4 kg 16,3 kg 16,9kg 19,8 kg **Order number Set:** L-50446 L-50335 L-50349 L-50425 L-50426















SEDA-Umwelttechnik GmbH

Schwendter Str. 10 / 6345 Kössen / Tirol / Österreich UID-Nr.: ATU56621622 / FB-Nr.: FN 231790 v / FB-Gericht: Innsbruck Certifled company according to DIN EN ISO 9001 +43 5375 6318-0

F: +43 5375 6318-9

E: info@seda.at

W: www.seda-international.com